



INSTRUCTIONS FOR USE

USES: FirmaFlex is great for cornices, arches, and wall-hung headboards. It is not recommended for use as a mounting board alone, unless it is supported with a face board.

SAWING: TABLE SAWS NOT RECOMMENDED!! Especially avoid carbide tip. Use manual rotary cutter (65mm blade!) for straight cuts.

Jigsaw recommended for intricate cuts; use blades designed for wood, not metal, that are for fine finish cutting (small teeth)

SQUARING: Check FirmaFlex for squareness before beginning project. Occasionally, squaring may be needed.

ASSEMBLING: Use screws, or pneumatic nailing tools with brad nails or finishing nails. Select the FirmaFlex side with best appearance.

GLUING: Use thick, tacky glue or hot glue. Avoid yellow wood glue and solvent-based glues.

COVERING: Use a fine wire upholstery staple gun, with staple length appropriate to the project you're doing

SPLICING: Butt two edges together, affix with hot glue. Then splice with staples, flip over and staple again from back side.

HINGING: Use manual rotary cutter to slice halfway through the material. Fold material in to create its own hinge.

Instrucciones para usar FirmaFlex™

CORTAR: **SIERRA DE MESA NO ES RECOMENDABLE!!!**

Especialmente evitar sierra de carburo

Se recomienda cortadora manual giratoria para cortes rectos.

Se recomienda sierra de vaiven para cortes intrincados.

CUADRAR: Chequear FirmaFlex para estar seguro que las orillas estan rectas antes de comenzar el proyecto. Ocasionalmente hay que enderezar las orillas.

ENSAMBLAJE: Utilizar tornillos o martillo neumatico con puntillas o clavos especiales para terminado.

PEGAMENTO: Usar un pegamento espeso o pegante caliente.

Evitar usar pegantes amarillos o pegantes que son a vase de solventes.

COVERTURA: Utilizar una engrapadora fina para tapiceria, con grapas de largo adecuado para el proyecto.

PARA UNIR: Poner 2 orillas juntas y unir con grapas, voltear el material y engarpar de nuevo por la parte trasera. Se recomienda poner pegante en las orillas antes de engrapar.

VISAGRA: Utilizando una guia recta, cortar parcialmente atravez del material con una cortadora manual giratoria. Doblar el material para crear su propia visagra.